4991

Technical sheet

Recommended use : Covers and Lagging, Separation curtains

Comments : Indoor use only

Due to the infinite number of applications, the customer should test and approve that the product is suitable. This technical data sheet can be modified according to technical evolution.

/!\White color (004) Tear strength : 4.5/2.5 daN

Characteristics	Values		11	Chan da ada
	Warp	Weft	Units	Standards
General characteris	tics			
Weight	600 (+/- 50 g)		g/m²	NF EN ISO 2286-2A
Base cloth	Fiberglass			
Coating	PVC			
Width	160		cm	
Roll length	50		ml	
Fabric resistance				
Tensile strength	170	170	daN/5cm	NF EN ISO 1421
Tear strength	6	3	daN	NF EN ISO 4674-2
Adhesion	8		daN/5cm	PILab02
Fire resistance	М	1		NF P 92 503







SAINT CLAIR TEXTILES

.....

415, avenue de Savoie F-38110 Saint-Clair-de-la-Tour Tel. (+33) 04 74 83 51 00 www.saintclairtextiles.com



Values may vary in a tolerance of +/-10%. Specification maybe modified and are subject to manufacturer's requisites. Product compatibility to the application is reserved to the users' appraisal. The buyer of our products is responsible for checking the validity of the above data.