

Arcade FR

Technical sheet

Recommended use : Small structures, Terrace awnings, Awnings, Sail shade

Characteristics	Values				Units	Standards
	Warp		Weft			
General characteristics						
Base cloth	550 dTex PES HT 495 den					
Coating	PVC Lowick coating both side					
Finish	Cleangard lacquer both sides					
Weight	500				g/m ²	ISO 3801
Width	150	150	302	302	cm	
Roll length	30	60	30	60	ml	

Fabric resistance

Tensile strength	150	150	daN/5cm	NF EN ISO 1421
Tear strength	15	15	daN	DIN 53.363
Adhesion	7		daN/5cm	NF EN ISO 2411
Elongation under load	<1	<3	%	NF EN 15619
Residual deformation	<0.4	<1.2	%	NF EN 15619
Cold resistance	-30		°C	NF EN 1876-2
Warm resistance	70		°C	[24h]
Fire resistance	M2			NF P 92 503
	B1			DIN 4102
	BS			BS 7837
	B-S2-D0			Euroclasses EN 13501-1
	NFPA 701			NFPA 701
	CSFM Title19			CSFM Title 19

SAINT CLAIR
TEXTILES

5 ANS
YEARS
GARANTIE - WARRANTY

SYSTEM
LOWICK

FINITION
CLEANGARD



REACH
COMPLIANCE

MADE IN
FRANCE

SAINT CLAIR TEXTILES

415, avenue de Savoie

F-38110

Saint-Clair-de-la-Tour

Tel. (+33) 04 74 83 51 00

Fax (+33) 04 74 83 51 01

www.saintclairtextiles.com



Values may vary in a tolerance of +/-10%. Specification maybe modified and are subject to manufacturer's requisites. Product compatibility to the application is reserved to the users' appraisal. The buyer of our products is responsible for checking the validity of the above data.