

Blockbuster

Technical sheet

Recommended use : Banners, Signage, Pole banners

Range :

Printing : digital inkjet printing

Printable side : Both side

Ink : Solvent, Eco-solvent, UV, Latex Ink

Characteristics	Values			Units	Standards
	Warp				
General characteristics					
Thickness	0.57			mm	ISO 5084
Base cloth	1100 dTex PES HT 990 den				
Coating	PVC Lowick coating both side				
Finish	Inkjet lacquer both side				
Weight	750			g/m ²	ISO 3801
Translucency	0			%	XPT 54199
Width	106	320	320	cm	
Roll length	30	30	60	ml	

Fabric resistance

Tensile strength	210	200	daN/5cm	NF EN ISO 1421
Tear strength	25	20	daN	EN 17679 / DIN 53363
Adhesion	9		daN/5cm	NF EN ISO 2411
Cold resistance	-30		°C	NF EN 1876-2
Warm resistance	70		°C	(24h)

SYSTEM
LOWICK



RESOURCE

REACH
COMPLIANCE

MADE IN
FRANCE

SAINT CLAIR TEXTILES

415, avenue de Savoie
F-38110

Saint-Clair-de-la-Tour
Tel. (+33) 04 74 83 51 00

www.saintclairtextiles.com

