

# ECOMESH

## Technical sheet

Recommended use : Window backdrop, Signage, Interior design

Range : EverGreen Textile

Printing : digital inkjet printing

Printable side : Outside

Ink : UV, Latex Ink, Solvent, Eco-solvent

Characteristics	Values		Units	Standards
	Warp	Weft		
<b>General characteristics</b>				
Thickness	0.32		mm	ISO 5084
Base cloth	Polyester			
Coating	EverGreen coating			
Finish	Inkjet lacquer one side			
Weight	205		g/m <sup>2</sup>	ISO 3801
Translucency	34		%	XPT 54199
Width	160	320	cm	
Roll length	30	50	ml	

## Fabric resistance

Tensile strength	180	180	daN/5cm	NF EN ISO 1421
Tear strength	35	35	daN	EN 17679 / DIN 53363
Fire resistance	M1			NF P 92 503
	B-s1-d0			Euroclasses EN 13501-1
	NFPA 701			NFPA 701
	ASTM E 84			ASTM E 84

## SAINT CLAIR TEXTILES

415, avenue de Savoie  
F-38110

Saint-Clair-de-la-Tour  
Tel. (+33) 04 74 83 51 00

[www.saintclairtextiles.com](http://www.saintclairtextiles.com)