

# JET 550

## Technical sheet

Recommended use : Banners, Signage, Pole banners

Range :

Printing : digital inkjet printing

Printable side : Outside

Ink : Solvent, Eco-solvent, UV, Latex Ink

Characteristics	Values		Units	Standards
	Warp	Weft		
<b>General characteristics</b>				
Thickness	0.47		mm	ISO 5084
Base cloth	1100 dTex PES HT 990 den			
Coating	PVC Lowick coating one side			
Finish	Inkjet lacquer one side			
Weight	560		g/m <sup>2</sup>	ISO 3801
Translucency	6		%	XPT 54199
Width	76 106 137 162 250 250 320 320		cm	
Roll length	30 30 30 30 30 60 30 60		ml	

## Fabric resistance

Tensile strength	210	200	daN/5cm	NF EN ISO 1421
Tear strength	25	20	daN	EN 17679 / DIN 53363
Adhesion	7		daN/5cm	NF EN ISO 2411
Cold resistance	-30		°C	NF EN 1876-2
Warm resistance	70		°C	(24h)
Fire resistance	< 100		mm/min	DIN 75 200
	NFPA 701			NFPA 701

Certified for  
HP Latex Inks

SYSTEM  
LOWICK



RESOURCE

REACH  
COMPLIANCE

MADE IN  
FRANCE

## SAINT CLAIR TEXTILES

415, avenue de Savoie  
F-38110

Saint-Clair-de-la-Tour  
Tel. (+33) 04 74 83 51 00

[www.saintclairtextiles.com](http://www.saintclairtextiles.com)

