

JET 620

Technical sheet

Recommended use : Light box

Range :

Printing : digital inkjet printing

Printable side : Outside

Ink : Solvent, Eco-solvent, UV, Latex Ink

Characteristics	Values			Units	Standards
	Warp		Weft		
General characteristics					
Thickness	0.49			mm	ISO 5084
Base cloth	1100 dTex PES HT 990 den				
Coating	PVC Lowick coating one side				
Finish	Inkjet lacquer one side				
Weight	570			g/m ²	ISO 3801
Translucency	23			%	XPT 54199
Width	137	160	320	cm	
Roll length	30	30	60	ml	

Fabric resistance

Tensile strength	210	200	daN/5cm	NF EN ISO 1421
Tear strength	25	20	daN	EN 17679 / DIN 53363
Adhesion	9		daN/5cm	NF EN ISO 2411
Cold resistance	-30		°C	NF EN 1876-2
Warm resistance	70		°C	(24h)
Fire resistance	M2			NF P 92 503
	B1			DIN 4102
	NFPA 701			NFPA 701

Certified for
HP Latex Inks

SYSTEM
LOWICK



RESOURCE

REACH
COMPLIANCE

MADE IN
FRANCE

SAINT CLAIR TEXTILES

415, avenue de Savoie
F-38110

Saint-Clair-de-la-Tour
Tel. (+33) 04 74 83 51 00

www.saintclairtextiles.com

