

JET UP

Technical sheet

Recommended use : P.O.S, Signage, Hanging banners, Window backdrop, Roll-up

Range : EverGreen Textile

Printing : digital inkjet printing

Printable side : Outside

Ink : Solvent, Eco-solvent, UV, Latex Ink

Characteristics	Values		Units	Standards
	Warp	Weft		
General characteristics				
Thickness	0.33		mm	ISO 5084
Base cloth	Polyester			
Coating	EverGreen coating			
Finish	Inkjet lacquer one side			
Weight	260		g/m ²	ISO 3801
Translucency	16		%	XPT 54199
Width	90 106 137 162 320			cm
Roll length	30 30 30 30 60			ml

Fabric resistance

Tensile strength	150	180	daN/5cm	NF EN ISO 1421
Tear strength	20	25	daN	EN 17679 / DIN 53363
		M1		NF P 92 503
		B1		DIN 4102
Fire resistance		B-s1-d0		Euroclasses EN 13501-1
		NFPA 701		NFPA 701
		ASTM E 84		ASTM E 84

EVERGREEN
ECO-FRIENDLY TEXTILES



**PVC
FREE**



**SAFETY
OF TOYS**



SAINT CLAIR TEXTILES

415, avenue de Savoie
F-38110

Saint-Clair-de-la-Tour
Tel. (+33) 04 74 83 51 00

www.saintclairtextiles.com

