

JET 520 FR+

Technical sheet

Recommended use : Separation curtains, Banners, P.O.S, Signage, Stand

Range : Frontlit

Printing : digital inkjet printing

Printable side : Outside

Ink : Solvent, Eco-solvent, UV, Latex Ink

Characteristics	Values		Units	Standards
	Warp	Weft		
General characteristics				
Thickness	0.45		mm	ISO 5084
Base cloth	1100 dTex PES HT 990 den			
Coating	PVC Lowick coating one side			
Finish	Inkjet lacquer one side			
Weight	550		g/m ²	ISO 3801
Translucency	6		%	XPT 54199
Width	106 137 162 250 320		cm	
Roll length	30 30 30 60 60		ml	

Fabric resistance

Tensile strength	210	200	daN/5cm	NF EN ISO 1421
Tear strength	25	20	daN	EN 17679 / DIN 53363
Adhesion	7		daN/5cm	NF EN ISO 2411
Cold resistance	-30		°C	NF EN 1876-2
Warm resistance	70		°C	[24h]
Fire resistance	B-s2-d0			Euroclasses EN 13501-1

SYSTEM
LOWICK



RESOURCE

REACH
COMPLIANCE

MADE IN
FRANCE

SAINT CLAIR TEXTILES

415, avenue de Savoie
F-38110

Saint-Clair-de-la-Tour
Tel. (+33) 04 74 83 51 00

www.saintclairtextiles.com

