Update 12-05-2025

JET 901 BC

Technical sheet

Recommended use : Printed truck curtains, Truck side curtains

Comments : Bicolor - Endroit blanc (7325) / Envers gris (939)

Range : Truck

Printing : digital inkjet printing

Printable side : Outside

Ink : Solvent, UV, Latex Ink

Characteristics	Values		Units	Standards
	Warp	Weft		
General characteristics				
Thickness	0.72		mm	ISO 5084
Base cloth	1100 dTex PES HT 990 den			
Coating	PVC Lowick coating both side			
Finish	Inkjet lacquer one side - Grey back			
Weight	900		g/m²	ISO 3801
Translucency	0		%	XPT 54199
Width	300	300	cm	
Roll length	35	50	ml	
Fabric resistance				
Tensile strength	400	400	daN/5cm	NF EN ISO 1421
Tear strength	60	50	daN	EN 17679 / DIN 53363
Adhesion	10		daN/5cm	NF EN ISO 2411
Cold resistance	-30		°C	NF EN 1876-2
Warm resistance	70		°C	(24h)
Fire resistance	< 100		mm/min	DIN 75 200

SAINT CLAIR TEXTILES

415, avenue de Savoie

F-38110

Saint-Clair-de-la-Tour

Tel. (+33) 04 74 83 51 00

www.saintclairtextiles.com

Values may vary in a tolerance of +/-10%. Specification maybe modified and are subject to manufacturer's requisites. Product compatibility to the application is reserved to the users' appraisal. The buyer of our products is responsible for checking the validity of the above data.