Update 20-01-2026

JET TEX ACOUSTIC

Technical sheet

권장용도 : Suspended acoustic frames, Acoustic screens, Acoustic panels, Acoustic walls

: EverGreen Textile

: Numérique Jet d'encre

: Extérieur du rouleau

: UV, Latex Ink, Solvent

Characteristics	Values		Units	Standards
	Warp	Weft		
일반적 특성				
두께	0.34		mm	ISO 5084
기본 직물	Polyester			
코팅	EverGreen coating			
마감	Printable one side			
중량	235		g/m²	ISO 3801
	20		%	XPT 54199
	aw jusqu'à 1.00 (selon configuration, nous consulter)			ISO 354
Width	160	320	cm	
Roll length	30	30	ml	
직물 저항성				
인장강도	70	120	daN/5cm	NF EN ISO 1421
인열강도	7	20	daN	EN 17679 / DIN 53363
내화성능	M1 (all color)			NF P 92 503
	B1 (white color)			DIN 4102
	B-s1-d0 (white color)			Euroclasses EN 13501-1
	NFPA (white color)			NFPA 701
	ASTM E 84 (white color)			ASTM E 84

SAINT CLAIR TEXTILES

415, avenue de Savoie

F-38110

Saint-Clair-de-la-Tour

Tel. (+33) 04 74 83 51 00

www.saintclairtextiles.com

Values may vary in a tolerance of +/-10%. Specification maybe modified and are subject to manufacturer's requisites. Product compatibility to the application is reserved to the users' appraisal. The buyer of our products is responsible for checking the validity of the above data.