

JET UP BC

Technical sheet

Recommended use : P.O.S, Signage, Hanging banners, Window backdrop, Roll-up

Range : EverGreen Textile

Printing : digital inkjet printing

Printable side : Outside

Ink : Solvent, Eco-solvent, UV, Latex Ink

Characteristics	Values		Units	Standards
	Warp	Weft		
General characteristics				
Thickness	0.34		mm	ISO 5084
Base cloth	Polyester			
Coating	EverGreen coating			
Finish	Inkjet lacquer one side - Grey back			
Weight	330		g/m ²	ISO 3801
Translucency	0		%	XPT 54199
Width	90	106 137 162	320 cm	
Roll length	50	50 50 50	60 ml	

Fabric resistance

Tensile strength	150	180	daN/5cm	NF EN ISO 1421
Tear strength	20	25	daN	DIN 53.363
Fire resistance	M1			NF P 92 503
	B1			DIN 4102
	B-s1-d0			Euroclasses EN 13501-1
	NFPA 701			NFPA 701
	ASTM E 84			ASTM E 84



SAFETY
OF TOYS



SAINT CLAIR TEXTILES

415, avenue de Savoie

F-38110

Saint-Clair-de-la-Tour

Tel. (+33) 04 74 83 51 00

Fax (+33) 04 74 83 51 01

www.saintclairtextiles.com

