Update 20-01-2026

# JET UP BC

## Technical sheet

권장용도 : P.O.S, Signage, Hanging banners, Window backdrop, Roll-up

: EverGreen Textile

: Numérique Jet d'encre

: Extérieur du rouleau

: Solvent, Eco-solvent, UV, Latex Ink

| Characteristics | Values | | Units | Standards |
|---|---|---|---|---|
| | Warp | Weft | | |
| **일반적 특성** | | | | |
| 두께 | 0.34 | | mm | ISO 5084 |
| 기본 직물 | Polyester | | | |
| 코팅 | EverGreen coating | | | |
| 마감 | Inkjet lacquer one side - Grey back | | | |
| 중량 | 300 | | g/m² | ISO 3801 |
| | 0 | | % | XPT 54199 |
| Width | 90 106 137 162 320 | | cm | |
| Roll length | 30 30 30 30 60 | | ml | |
| **직물 저항성** | | | | |
| 인장강도 | 150 | 180 | daN/5cm | NF EN ISO 1421 |
| 인열강도 | 20 | 25 | daN | EN 17679 / DIN 53363 |
| 내화성능 | M1 | | | NF P 92 503 |
| | B1 | | | DIN 4102 |
| | B-s1-d0 | | | Euroclasses EN 13501-1 |
| | NFPA 701 | | | NFPA 701 |
| | ASTM E 84 | | | ASTM E 84 |


**SAINT CLAIR TEXTILES**

415, avenue de Savoie

F-38110

Saint-Clair-de-la-Tour

Tel. (+33) 04 74 83 51 00

www.saintclairtextiles.com



*Values may vary in a tolerance of +/-10%. Specification maybe modified and are subject to manufacturer's requisites. Product compatibility to the application is reserved to the users' appraisal. The buyer of our products is responsible for checking the validity of the above data.*