

JET UP

Technical sheet

Recommended use : P.O.S, Signage, Hanging banners, Window backdrop, Roll-up

Range : EverGreen Textile

Printing : digital inkjet printing

Printable side : Outside

Ink : Solvent, Eco-solvent, UV, Latex Ink

Characteristics	Values		Units	Standards
	Warp	Weft		
General characteristics				
Thickness	0.33		mm	ISO 5084
Base cloth	Polyester			
Coating	EverGreen coating			
Finish	Inkjet lacquer one side			
Weight	280		g/m ²	ISO 3801
Translucency	16		%	XPT 54199
Width	90	106 137 162 320	cm	
Roll length	50	50 50 50 60	ml	

Fabric resistance

Tensile strength	150	180	daN/5cm	NF EN ISO 1421
Tear strength	20	25	daN	DIN 53.363
Fire resistance	M1			NF P 92 503
	B1			DIN 4102
	B-s1-d0			Euroclasses EN 13501-1
	NFPA 701			NFPA 701
	ASTM E 84			ASTM E 84

SAINT CLAIR TEXTILES

415, avenue de Savoie

F-38110

Saint-Clair-de-la-Tour

Tel. (+33) 04 74 83 51 00

Fax (+33) 04 74 83 51 01

www.saintclairtextiles.com