

LAC 650 SL

Technical sheet

: Pergolas, Auvents, Voiles d'ombrage, Chapiteaux, Glamping, Portes souples

Characteristics	Values						Units	Standards
	Warp			Weft				
Caractéristiques générales								
	0.52						mm	ISO 5084
□□	1100 dTex PES HT							
	990 den							
	PVC Lowick enduction 2 faces							
	Cleangard double face							
	680						g/m ²	ISO 3801
Width	250	250	250	300	300	300	cm	
Roll length	30	60	250	30	60	250	ml	

Résistance du tissu

	260	250	daN/5cm	NF EN ISO 1421
	32	28	daN	EN 17679 / DIN 53363
	8		daN/5cm	NF EN ISO 2411
	<1	<2	%	NF EN 15619
	<0.4	<0.8	%	NF EN 15619
	-30		°C	NF EN 1876-2
	70		°C	(24h)
	M2			NF P 92 503
	B1			DIN 4102
	BS			BS 7837
	B-s2-d0			Euroclasses EN 13501-1
	T2 [white]			NF EN 14115
	NFPA 701			NFPA 701
	CSFM Title19			CSFM Title 19

dsc_garantie_5_KO.jpg

SYSTEM
LOWICK

FINITION
CLEANGARD



REACH
COMPLIANCE

MADE IN
FRANCE

SAINT CLAIR TEXTILES

415, avenue de Savoie
F-38110

Saint-Clair-de-la-Tour
Tel. (+33) 04 74 83 51 00

www.saintclairtextiles.com

