Update 26-10-2026

LAC 901 DW

Technical sheet

Recommended use : Flexible Tank, Tank sealing

Comments : Tested and certified in compliance with the requirements of regulations: 10/2011, 1245/2020 and 1935/2004 of the European Commission regarding plastic materials and objects intended to come into repeated contact with Drinking water.

Grey side exposed to contact with food.

Characteristics	Values		Units	Standards
	Warp	Weft		
General characteristics				
Base cloth	1100 dTex PES HT 990 den			
Coating	PVC Lowick coating both side			
Finish	Cleangard lacquer both sides			
Weight	900		g/m²	ISO 3801
Width	300	300	cm	
Roll length	60	200	ml	
Fabric resistance				
Tensile strength	400	400	daN/5cm	NF EN ISO 1421
Tear strength	55	55	daN	EN 17679 / DIN 53363
Adhesion	12		daN/5cm	NF EN ISO 2411
Puncture resistance	9		kN	NF EN 12236
Cold resistance	-30		°C	NF EN 1876-2
Heat resistance	70		°C	(24h)

SAINT CLAIR TEXTILES

415, avenue de Savoie

F-38110

Saint-Clair-de-la-Tour

Tel. (+33) 04 74 83 51 00

www.saintclairtextiles.com

Values may vary in a tolerance of +/-10%. Specification maybe modified and are subject to manufacturer's requisites. Product compatibility to the application is reserved to the users' appraisal. The buyer of our products is responsible for checking the validity of the above data.