

아케이드 방염

Technical sheet

: Tentes légères - pliantes, Auvents, Stores corbeilles, Voiles d'ombrage

Characteristics	Values						Units	Standards
	Warp			Weft				
Caractéristiques générales								
□□	550 dTex PES HT							
	495 den							
	PVC Lowick enduction 2 faces							
	Cleangard double face							
	500						g/m²	ISO 3801
Width	150	150	250	250	302	302	cm	
Roll length	30	60	30	60	30	60	ml	

Résistance du tissu

	150	150	daN/5cm	NF EN ISO 1421
	15	15	daN	EN 17679 / DIN 53363
	7		daN/5cm	NF EN ISO 2411
	<1	<3	%	NF EN 15619
	<0.4	<1.2	%	NF EN 15619
	-30		°C	NF EN 1876-2
	70		°C	(24h)
	M2			NF P 92 503
	B1			DIN 4102
	BS			BS 7837
	B-s2-d0			Euroclasses EN 13501-1
	NFPA 701			NFPA 701
	CSFM Title19			CSFM Title 19



SAINT CLAIR TEXTILES

415, avenue de Savoie
F-38110

Saint-Clair-de-la-Tour
Tel. (+33) 04 74 83 51 00

www.saintclairtextiles.com

