



# JET 620

## BACKLIT 17 oz/yd<sup>2</sup>



FLAME RETARDANT

### APPLICATIONS

- ONE SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent / UV and Latex inks
- INDOOR / OUTDOOR: neon sign / backlit advertising / lightbox

### PRODUCT PACKAGING

|                   |           |                        |
|-------------------|-----------|------------------------|
| WIDE FORMAT       | 54" / 64" | Rolls of: 98' (30 lm)  |
| SUPER WIDE FORMAT | 126"      | Rolls of: 197' (60 lm) |

### PRODUCT CHARACTERISTICS

|                                    |   |
|------------------------------------|---|
| WEIGHT                             | 17 oz/yd <sup>2</sup> (560 g/m <sup>2</sup> ) |
| BASE CLOTH                         | High tenacity polyester<br>1100 Dtex          |
| COATING                            | PVC coating<br>System LOWICK                  |
| FINISH                             | Satin Inkjet lacquer<br>One side              |
| COLOUR                             | White 7325                                    |
| THICKNESS                          | 19 mils<br>(0.49 mm)                          |
| TRANSLUCENCY<br>XPT 54 199         | 23 %  |
| TENSILE STRENGTH<br>NF EN ISO 1421 | 240 x 228 lbs / inch<br>(210 / 200 daN)       |
| TEAR STRENGTH<br>DIN 53363         | 56 x 45 lbs<br>(25 / 20 daN)                  |
| TEMPERATURE<br>STABILITY           | -30°C to +70°C<br>-22°F to +158°F             |
| ADHESION<br>NF EN ISO 2411         | 0,9 lbs /inch                                 |
| FIRE RETARDENT                     | M2 / B1<br>NFPA 701                           |

Average values +/- 10%



SYSTEM  
LOWICK



Certified for  
HP Latex Inks



Company with management system certified by DNV-GL  
ISO 9001 · ISO 14001



[www.dickson-coatings.com](http://www.dickson-coatings.com)  
[www.evergreen-fabrics.com](http://www.evergreen-fabrics.com)