



BLOCKBUSTER

BLACKOUT 22 oz/yd²

APPLICATIONS

- BOTH SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent / UV and Latex inks
- OUTDOOR: billboards / banners / signage / POS / pole banners / hanging banners

PRODUCT PACKAGING

WIDE FORMAT	42" / 54" / 126"	Rolls of: 98' (30 lm)
SUPER WIDE FORMAT	126"	Rolls of: 197' (60 lm)

PRODUCT CHARACTERISTICS

WEIGHT	22 oz/yd ² (750 g/m ²)
BASE CLOTH	High tenacity polyester 1100 Dtex
COATING	PVC coating System LOWICK
FINISH	Satin Inkjet lacquer Both side
COLOUR	White 7325
THICKNESS	22 mils (0.57 mm)
TRANSLUCENCY XPT 54 199	0 %
TENSILE STRENGTH NF EN ISO 1421	240 x 228 lbs / inch (210 / 200 daN)
TEAR STRENGTH DIN 53363	56 x 45 lbs (25 / 20 daN)
TEMPERATURE STABILITY	-30°C to +70°C -22°F to +158°F
ADHESION NF EN ISO 2411	1 lbs / inch
FIRE RETARDENT	-

Average values +/- 10%



SYSTEM
LOWICK



Company with management system certified by DNV-GL
ISO 9001 · ISO 14001



www.dickson-coatings.com
www.evergreen-fabrics.com