



OPTIKA PRINT

MESH 9 oz/yd²



FLAME RETARDANT

APPLICATIONS

- ONE SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent UV and Latex inks
- INDOOR / OUTDOOR: scaffolding building wraps / decoration (stands / shops) / false ceilings

PRODUCT PACKAGING

| | | |
|--------------------------|------|------------------------|
| SUPER WIDE FORMAT | 126" | Rolls of: 164' (50 lm) |
|--------------------------|------|------------------------|

PRODUCT CHARACTERISTICS

| | |
|---|--|
| WEIGHT | 9 oz/yd ² (300 g/m ²) |
| BASE CLOTH | High tenacity polyester 1100 Dtex |
| COATING | PVC coating |
| FINISH | Inkjet lacquer One side |
| COLOUR | White |
| THICKNESS | 18 mils (0.45 mm) |
| TRANSLUCENCY XPT 54 199 | 19,5 % |
| TENSILE STRENGTH NF EN ISO 1421 | 160 x 206 lbs / inch (140 / 180 daN) |
| TEAR STRENGTH DIN 53363 | 67 x 67 lbs (30 / 30 daN) |
| TEMPERATURE STABILITY | -30°C to +70°C -22°F to +158°F |
| ADHESION NF EN ISO 2411 | 0,7 lbs /inch |
| FIRE RETARDENT | M1 |

Average values +/- 10%



Company with management system certified by DNV-GL
ISO 9001 · ISO 14001



www.dickson-coatings.com
www.evergreen-fabrics.com