



FRONTLIT

JET 520



550 g/m²



FLAME
RETARDANT



IN / OUT

APPLICATIONS :

*Banderole, signalétique, P.L.V, habillage de stand,
rideau de séparation*

Banner, signage, P.O.S, stand, separation curtain

[DE] ANWENDUNG :

Bandenwerbung, Signage, Trennvorhänge, P.O.S, Messestand Dekore

[ES] APLICACIONES :

Pancartas, señalización, grafica en punto de venta, decoración de stands en ferias, cortinas separadoras

[IT] APPLICAZIONI :

Striscioni pubblicitari, segnaletica, P.L.V, allestimenti decorativi stand, tende divisorie



Bâche frontlit ignifuge pour les ERP

FR Frontlit banner for public places

Schwerentflammbares Frontlit Banner für öffentlichen Räumen

Pancartas y banderolas para espacios públicos

Banner frontale ignifugo per spazi pubblici

JET 520

Base cloth <i>Support / Trägergewebe / Soporte / Supporto</i>	1100 dTex PES HT
Coating <i>Enduction / Beschichtung / Revestimiento / Spalmatura</i>	PVC Lowick coating one side
Finish <i>Finition / Ausrüstung / Acabado / Finizione</i>	Inkjet lacquer one side
Total weight <i>Poids Total / Gesamtgewicht / Peso total / Peso totale</i>	550 g/m ²
Thickness <i>Epaisseur / Materialdicke / Espesor / Spessore</i>	0.45 mm
Translucency > XPT 54199 <i>Translucidité / Transluzenz / Translucidez / Translucenza</i>	6 %
Tensile strength > NF EN ISO 1421 <i>Résistance rupture / Reißfestigkeit / Resistencia a la rotura / Resistenza alla rottura</i>	210 / 200 daN / 5cm
Tear strength > DIN 53363 <i>Résistance déchirure / Weiterreißfestigkeit Resistencia al desgarro / Resistenza allo strappo</i>	25 / 20 daN
Adhesion > NF EN ISO 2411 <i>Adhérence / Haftung / Adherencia / Aderenza</i>	7 daN / 5 cm
Temperature resistance > NF EN 1876-2 <i>Températures d'utilisation / Temperaturbeständigkeit Resistencia máxima a la temperatura / Resistenza alla temperatura</i>	-30°C +70°C (24h)
Flame Retardancy > NF P 92503 / Euroclasses EN 13501-1 <i>Ignifugation / Brennverhalten / Ignifugación / Ignifugazione</i>	M1 / B-S2-D0



Wide Format	1.06 / 1.37 / 1.62 m	30 lm
Super Wide Format	2.50 / 3.20 m	60 lm



⋮ Average values. The buyer of our products is responsible for checking the validity of the above data, on the latest data sheet available at www.saintclairtextiles.com



SCTEX.FR/JET520

SYSTEM
LOWICK

MADE IN
FRANCE



REACH
COMPLIANCE



SAINT CLAIR TEXTILES
www.saintclairtextiles.com

