



BACKLIT

JET 620



570 g/m²



FLAME
RETARDANT



IN / OUT

APPLICATIONS :

Enseigne lumineuse

Light box

[DE] ANWENDUNG :
Leuchtkasten

[ES] APLICACIONES :
Cajas de luz

[IT] APPLICAZIONI :
Insegne luminose

+ *Bâche backlit : excellent
équilibre « jour/nuit »*

*Backlit banner with an excellent
"night & day" balance*

*Backlit Banner mit einem ausgezeichnetem "Tag &
Nacht" Gleichgewicht*

*Una pancarta retroilluminada con un excelente
balance «día y noche»*

*Striscione retroilluminato con pizzo «giorno e notte»
in equilibrio*

JET 620

| | |
|--|--------------------------------|
| Base cloth <i>Support / Trägergewebe / Soporte / Supporto</i> | 1100 dTex PES HT |
| Coating <i>Enduction / Beschichtung / Revestimiento / Spalmatura</i> | PVC Lowick coating one side |
| Finish <i>Finition / Ausrüstung / Acabado / Finizione</i> | Inkjet lacquer one side |
| Total weight <i>Poids Total / Gesamtgewicht / Peso total / Peso totale</i> | 570 g/m ² |
| Thickness <i>Epaisseur / Materialdicke / Espesor / Spessore</i> | 0.49 mm |
| Translucency > XPT 54199 <i>Translucidité / Transluzenz / Translucidez / Translucenza</i> | 23 % |
| Tensile strength > NF EN ISO 1421 <i>Résistance rupture / Reißfestigkeit / Resistencia a la rotura / Resistenza alla rottura</i> | 210 / 200 daN / 5cm |
| Tear strength > DIN 53363 <i>Résistance déchirure / Weiterreißfestigkeit Resistencia al desgarro / Resistenza allo strappo</i> | 25 / 20 daN |
| Adhesion > NF EN ISO 2411 <i>Adhérence / Haftung / Adherencia / Aderenza</i> | 9 daN / 5 cm |
| Temperature resistance > NF EN 1876-2 <i>Températures d'utilisation / Temperaturbeständigkeit Resistencia máxima a la temperatura / Resistenza alla temperatura</i> | -30°C +70°C (24h) |
| Flame Retardancy > NF P 92503 / DIN 4102 / NFPA701 <i>Ignifugation / Brennverhalten / Ignifugación / Ignifugazione</i> | M2 / B1 NFPA701 |



| | | |
|-------------------|---------------|-------|
| Wide Format | 1.37 / 1.62 m | 30 lm |
| Super Wide Format | 3.20 m | 60 lm |



⋮ Average values. The buyer of our products is responsible for checking the validity of the above data, on the latest data sheet available at www.saintclairtextiles.com



SCTEX.FR/JET620

SYSTEM
LOWICK

MADE IN
FRANCE



REACH
COMPLIANCE



SAINT CLAIR TEXTILES
www.saintclairtextiles.com

