

# RT 360 M1




SCTEX.FR/RT360



Base cloth <i>Support / Trägergewebe / Soporte / Supporto</i>	1100/550 dtex PES HT
Coating <i>Enduction / Beschichtung / Revestimiento / Spalmatura</i>	PVC
Finish <i>Finition / Ausrüstung / Acabado / Finizione</i>	Vernis MAT
Total weight <i>Poids Total / Gesamtgewicht / Peso total / Peso totale</i>	385 g/m²
Tensile strength > NF EN ISO 1421 <i>Résistance rupture / Reissfestigkeit / Resistencia a la rotura / Resistenza alla rottura</i>	270/180 daN / 5cm
Tear strength > DIN 53363 <i>Résistance déchirure / Weiterreissfestigkeit / Resistencia al desgarro / Resistenza allo strappo</i>	50/33 daN
Adhesion > NF EN ISO 2411 <i>Adhérence / Haftung / Adherencia / Aderenza</i>	7 daN / 5 cm
Temperature resistance > NF EN 1876-2 <i>Températures d'utilisation / Temperaturbeständigkeit / Resistencia máxima a la temperatura / Resistenza alla temperatura</i>	-30°C +70°C (24h)
Flame Retardancy > NF P 92503 / Euroclasses EN 13501-1 <i>Ignifugation / Brennverhalten / Ignifugación / Ignifugazione</i>	M1 B-S2-D0

... Average values. The buyer of our products is responsible for checking the validity of the above data, on the latest data sheet available at [www.saintclairtextiles.com](http://www.saintclairtextiles.com)



**867** (RAL 9010)  
3.00 m x 60 ml



**7458** (RAL 1015)  
3.00 m x 60 ml

## ADVANTAGES

AVANTAGES / VORTEILE / VENTAJAS / VANTAGGI



M1

**High fire resistance**  
Haute résistance au feu  
Hohe Brandfestigkeit  
Alta resistencia al fuego  
Alta resistenza al fuoco



**High tear resistance**  
Haute résistance à la déchirure  
Hohe Weiterreißfestigkeit  
Alta resistencia al desgarro  
Alta resistenza allo strappo



**Light**  
Léger  
Licht  
Luz  
Leggero



**Other colours on special production**  
Autres coloris sur fabrications spéciales  
Andere Farbe mit Sonderproduktion möglich  
Otros colores bajo pedido mínimo  
Colori diversi per produzioni speciali



**939**  
3.00 m x 60 ml

# 4991



SCTEX.FR/4991



Base cloth <i>Support / Trägergewebe / Soporte / Supporto</i>	Verre Fibreglass
Width <i>Laize / Breite / Ancho / Altezza</i>	1.60 m
Length <i>Longueur / Rollenlänge / Largo / Lunghezza</i>	50 ml
Coating <i>Enduction / Beschichtung / Revestimiento / Spalmatura</i>	PVC 2 sides
Total weight <i>Poids Total / Gesamtgewicht / Peso total / Peso totale</i>	600 g/m² (+/- 50)
Tensile strength > NF EN ISO 1421 <i>Résistance rupture / Reissfestigkeit / Resistencia a la rotura / Resistenza alla rottura</i>	170 / 170 daN / 5cm
Tear strength > DIN 53363 <i>Résistance déchirure / Weiterreissfestigkeit / Resistencia al desgarro / Resistenza allo strappo</i>	6 / 3 daN
Adhesion > Internal procedure P1Lab02 <i>Adhérence / Haftung / Adherencia / Aderenza</i>	8 daN / 5 cm
Flame Retardancy > NF P 92503 Ignifugation / Brennverhalten / Ignifugación / Ignifugazione	M1

... Average values. The buyer of our products is responsible for checking the validity of the above data, on the latest data sheet available at [www.saintclairtextiles.com](http://www.saintclairtextiles.com)



**693**  
1.60 m x 50 ml

## ADVANTAGES

AVANTAGES / VORTEILE / VENTAJAS / VANTAGGI



M1

**Excellent resistance to flames and perforation**  
Résistance à la flamme exceptionnelle, pas de percement du matériau  
Einzigartige Feuerfestigkeit, keine Durchlöcherung des Werkstoffs  
Magnífica resistencia a las llamas sin perforación del material  
Resistenza eccezionale alla fiamma nessuna perforazione del materiale



**Very good dimensional stability under heat**  
Très bonne stabilité dimensionnelle sous l'effet de la chaleur  
Hervorragende Formbeständigkeit unter Wärmeeinwirkung  
Elevada estabilidad dimensional bajo el efecto del calor  
Stabilità dimensionale molto buona sotto l'effetto del calore



**For indoor use only**  
Réservé à un usage intérieur uniquement  
Nur für den Gebrauch im Innenbereich bestimmt  
Reservado al uso únicamente en interior  
Riservato esclusivamente per un uso interno



**SAINT CLAIR**  
TEXTILES



## M1 - HIGH FIRE RESISTANCE

**RT 360 M1**  
LIGHTWEIGHT RANGE

**4991**  
FIBERGLASS



**APPLICATIONS :**  
Flame retardant curtains, flexible partitions

*[FR] Rideaux de séparation ignifuges, cloisons souples*

*[DE] Schwer entflammbare Vorhänge, flexible Trennwände*

*[ES] Cortinas ignifugas, particiones flexibles*

*[IT] Tende ignifughe, pareti divisorie flessibili*



[SCTEX.FR/M1](http://SCTEX.FR/M1)



**SAINT CLAIR TEXTILES**

415, avenue de Savoie  
F-38110 Saint-Clair-de-la-Tour  
Tel. (+33) 04 74 83 51 00  
Fax (+33) 04 74 83 51 01



[www.saintclairtextiles.com](http://www.saintclairtextiles.com)