

TOPCARE

Base cloth <i>Support / Trägergewebe / Soporte / Supporto</i>	280 dtex PES HT 252 den
Width <i>Laize / Breite / Ancho / Altezza</i>	3.00 m 118 in
Length <i>Longueur / Rollenlänge / Largo / Lunghezza</i>	30-60 ml 33-66 yd
Thickness <i>Epaisseur / Dicke / Espesor / Spessore</i>	0.3 mm 11.81 mils
Coating <i>Enduction / Beschichtung / Revestimiento / Spalmatura</i>	PVC (LOWICK)
Finish <i>Finition / Ausrüstung / Acabado / Finizione</i>	Cleangard
Total weight <i>Poids Total / Gesamtgewicht / Peso total / Peso totale</i>	310 g/m ² 9 oz/yd²
Tensile strength > NF EN ISO 1421 <i>Résistance rupture / Reissfestigkeit / Resistencia a la rotura / Resistenza alla rottura</i>	137 / 160 lbs/inch
Tear strength > DIN 53363 <i>Résistance déchirure / Weiterreissfestigkeit / Resistencia al desgarro / Resistenza allo strappo</i>	31 / 27 lbs
Adhesion > NF EN ISO 2411 <i>Adhérence / Haftung / Adherencia / Aderenza</i>	7 lbs/inch
Temperature resistance > NF EN 1876-1 <i>Températures d'utilisation / Temperaturbeständigkeit / Resistencia máxima a la temperatura / Resistenza alla temperatura</i>	-22°F +158°F (24h)

... Average values. The buyer of our products is responsible for checking the validity of the above data, on the latest data sheet available at www.saintclairtextiles.com

ADVANTAGES

AVANTAGES / VORTEILE / VENTAJAS / VANTAGGI



All-weather resistant
Résistant aux intempéries
Wetterbeständig
Resistente a la intemperie
Resistente alle intemperie



Tear strength
Résistant à la déchirure
Reißfestigkeit
Resistencia al desgarro
Resistenza allo strappo



Mold resistant
Résistant aux moisissures
Schimmelresistent
Resistente al moho
Resistente alla muffa



UPF 50+
UV protection
Protège des UV
UV-Schutz
Protección UV
Protezione UV

**SYSTEM
LOWICK**

**FINITION
CLEANGARD**



Technical data,
Certificats ...



SCTEX.FR/TOPCA-US

SAINT CLAIR
TEXTILES

www.saintclairtextiles.com

NORTH AMERICA
LOGISTICS CENTER SAINT CLAIR TEXTILES

2702-C South Dixie Highway
Dalton, GA 30720

us-order@saintclairtextiles.com